


EN 14785

BlmSchV Stufe 2

Regensburger BStV / Aachener BStV / Munchener BStV

ART.15a B-VG / Klimafonds / LRV

4 stelle DM.186 / Conto Termico 2.0




(Max) nominal heat output	6.3 kW
Minimum heat output	2.5 kW
Efficiency at Max	91.5 %
Efficiency at Min	92 %
Energy Efficiency Class (A++ / G scale)	A+
Energy Efficiency Index (EEI)	122 %
Seasonal space heating energy efficiency (ηs)	81 %
Temperature of exhaust smoke at Max	165 °C
Temperature of exhaust smoke at Min	103 °C
Particulate/OGC / Nox (nominal at 13%O2)	17 - 1 - 139 mg/Nm3
CO at 13% O2 at Min and at Max	0.055 - 0.007 %
CO2 at Min and at Max	7.4 - 12.8 %
Recommended draught at Max power	10 Pa
Minimum draught allowed for minimum power	5 Pa
Mass of smoke at Min and at Max	2.5 - 3.7 g/sec
Hopper capacity	24 l
Fuel dimensions	Ø 6mm L 3 ÷ 40mm
Hourly consumption at Min and at Max	0.6 - 1.45 kg/h *
Autonomy at Min and at Max	26 - 11 h *
Heatable volume m3	115 - 180 - 315 **
Combustion air inlet	Ø 50 mm
Air inlet	80 cm2
Smoke outlet	Ø 80 mm
Nominal electrical power (EN 60335-1).	49 W (max 380 W)
Supply voltage and frequency	230 Volt / 50 Hz
Net weight	90 kg
Distance from combustibile material (back/side/under)	50 mm / 100 mm / 0 mm
Distance from combustibile material (front/ceiling)	800 mm / 1000 mm

* Data that may vary depending on the type of pellets used.

**Heatable volume based on the requested power per m3 (respectively 55-35-20 W/m3)